

Productkaart volgens de Gedelegeerde Verordening (EU) nr. 65/2014 van de Commissie van 1 oktober 2013 en de Gedelegeerde Verordening (EU) nr. 66/2014 van de Commissie van 14 januari 2014

Naam of handelsmerk van de leverancier	SMEG
Productcode	KSGT63X
Jaarlijks energieverbruik (AEChood)	52.7 kWh/a
Energy efficiency class	A
Fluid Dynamic Efficiency (FDEhood)	31.3
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LEhood)	75.0 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	84.9 %
Grease Filtering Efficiency Class	C
Air Flow at minimum speed	270 m ³ /h
Air flow at maximum speed	482 m ³ /h
Air flow at boost speed	716 m ³ /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	47 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed	62 dB(A)
Airbourne acoustical A-weighted sound power emission at boost speed	70 dB(A)
Power consumption in stand-by mode	0.49 W
Time increase factor	0.9
Energie-efficiëntie-index	51.7
Measured air flow rate at best efficiency point	388 m ³ /h
Measured air pressure at best efficiency point	450 Pa
Measured electric power input at best efficiency point	155 W
Normal Power of the light system	3 W
Gemiddelde lichtsterkte van het licht op het kookoppervlak (Emiddle)	195 lux
Sound power level at highest setting	62 dB(A)

21 August 2023